

Order guide

recessed LED



SERIES		VERSION		LIGHT SOURCE			HOUSING	ELECTRICAL		
FAMILY	SIZE	VERSION	CONFIGURATION	SOURCE	COLOR TEMP	LUMENS	TYPE	WIRING	VOLTAGE	DRIVER
36 ArcForm 94 PureFX 97 Vectra	14 1' x 4' 22 2' x 2'	D1 Standard T-Grid D2 Slot T-Grid	ST Standalone	L LED	A 4000k B 3500k C 3000k	30 3000 lumens (ArcForm only) 36 3600 lumens 44 4400 lumens	S Standard	7 1 cct w/ dimming N 1 cct w/ dimming & battery pack*	1 120v 2 277v 3 347v*	E Philips Advance 0-10v (1% dim)
41 VersaForm 42 SilkSpace	14 1' x 4' 22 2' x 2'	D1 Standard T-Grid D2 Slot T-Grid (VersaForm only)			8A 80/4000k 8B 80/3500k 8C 80/3000k	K 1700 lumens (SilkSpace only) E 3000 lumens D 4000 lumens				
	24 2' x 4'					D 4000 lumens C 5200 lumens A 6800 lumens				
33 Shine	52 20" x 2" M2 600 x600mm	D1 Standard T-Grid				E 3000 lumens D 4000 lumens				
	54 20" x 4" M4 600 x1200mm					D 4000 lumens C 5200 lumens A 6800 lumens				

*Battery packs in 120-277v only, 347v with battery pack not available.

Note: QuickShip not available for "Hold for Release" or "Do Not Ship Before" orders.
Optional 6' flex whips and drywall kits available.

MAXIMUM 100 UNITS PER QUICKSHIP ORDER.

Questions? CS.ledalite@philips.com



Order guide

linear recessed & perimeter LED



SERIES		VERSION	LIGHT SOURCE			BODY				ELECTRICAL		
FAMILY	VERSION	DISTRIBUTION	SOURCE	COLOR TEMP	LUMENS	LENS	HOUSING	CEILING/TRIM	RUN LENGTH	WIRING	VOLTAGE	DRIVER
39 TruGroove Recessed	0 Straight Run	1 Symmetric-Performance	L LED	A 4000k	D 4000lm/4ft	Q Flush-Performance	S Standard	1 T-Grid	2'-20' in 2' increments	7 1 cct w/ dimming	1 120v 2 277v 3 347v*	E Philips Advance 0-10v (1% dim)
		8 Asymmetric-Performance (Flush lens only)		B 3500k	E 3000lm/4ft	R Regressed-Performance		3 Drywall Trimless		M 1cct w/ dimming & emergency		
		0 Symmetric-Definition		C 3000k	G 2200lm/4ft K 1500lm/4ft	L Flush-Definition M Regressed-Definition		4 Drywall Trim		N 1 cct w/ dimming & battery pack*		

SERIES		VERSION	LIGHT SOURCE			BODY				ELECTRICAL		
FAMILY	VERSION	DISTRIBUTION	SOURCE	COLOR TEMP	LUMENS	LENS	HOUSING	CEILING/TRIM	RUN LENGTH	WIRING	VOLTAGE	DRIVER
49 TruGroove Perimeter	0 Straight Run	8 Ambient	L LED	A 4000k	D 4100lm/4ft	Q Flush MesoOptics Lens	S Standard	N All Ceilings** (see table below)	2'-20' in 2' increments	7 1 cct w/ dimming	1 120v 2 277v 3 347v*	E Philips Advance 0-10v (1% dim)
		9 Graze		B 3500k C 3000k	E 3000lm/4ft G 2100lm/4ft K 1400lm/4ft	P Reverse Parabolic Optic w/Flush Lens				7 1 cct w/ dimming (EM & BP not available in Graze)		

*Battery packs in 120-277v only, 347v with battery pack not available. There are limitations on battery packs for 2' & 3' modules.

Note: QuickShip not available for "Hold for Release" or "Do Not Ship Before" orders.

MAXIMUM 500' PER QUICKSHIP ORDER.

Questions? CS.ledalite@philips.com

ENDSETS		SLOT & CEILING TRIM		
LEFT ENDSET	RIGHT ENDSET	SLOT HEIGHT	SLOT PANEL	CEILING TRIM
C Variable/Wall S Fixed/Pocket	C Variable/Wall S Fixed/Pocket	2 1.75" 4 4"	S Solid A Air Return	1 T-Grid 3 Drywall Trimless 4 Drywall Trim

**Example part number: 4908LBEQSN-16-7-1-E, S/S, 4S3



Order guide

linear suspended/surface LED



SERIES		VERSION		LIGHT SOURCE			OPTICS		BODY	ELECTRICAL			FINISH		MOUNTING	
FAMILY	VERSION	DISTRIBUTION	SOURCE	COLOR TEMP	LUMENS	LOWER OPTICS	UPPER OPTICS	MODULE LENGTH	WIRING TYPE	VOLTAGE	DRIVER	FINISH	ENDS	CEILING KIT	DROP LENGTH	
78 BoldPlay	0 Standard	6 Direct-Indirect	L LED	A 4000k B 3500k C 3000k	C 6500lm/4ft	Q MesoOptics Lens	N Lightguide	4' & 8'	7 1 cct w/dimming M 1 cct w/dimming & emergency N 1 cct w/dimming & battery pack*	1 120v 2 277v 3 347v*	E Philips Advance 0-10v (1% dim)	W Standard White T Titanium Silver B Black	Sculpted	A1 A2 A3 A5 A6-1 A6-2 A6-3	2' 24" adjustable 4' 48" adjustable 8' 96" adjustable 12' 144" adjustable	
					C 4600lm/4ft											
					E 3400lm/4ft											
75 Chopstick	0 Standard	5 Semi-Indirect			C 4800lm/4ft E 3400lm/4ft	Q MesoOptics Lens	N Lightguide	4', 6' & 8'				Flat				
24 FloatPlane	G Edge R Curve	5 Direct-Indirect			B 6000lm/4ft C 4500lm/4ft E 3200lm/4ft	A Acrylic diffusers	A 70% up G 75% down J 100% down	4', 6' & 8'					Sculpted	Surface (where available)		
12 Jump	0 Standard 1 Surface	1 Direct			C 4900lm/4ft E 3600lm/4ft G 2400lm/4ft	Q MesoOptics Lens	E Solid Side / No Perf P Pixel Perf S Splash Perf	4' & 8'					Luminous Sculpted			
22 MicroSquare gen2	0 Standard	1 Direct			G 2600lm/4ft K 1300lm/4ft	L Flush Silk Lens	N None	4', 6' & 8'					Solid Cube			
		3 Indirect			C 4700lm/4ft E 3400lm/4ft	N Solid Housing	Q Symmetric Wide-Throw Lens	4', 6' & 8'					Solid Cube			
		5 Indirect-Direct			B 5900lm/4ft C 4800lm/4ft E 3100lm/4ft	L Flush Silk Lens	Q Symmetric Wide-Throw Lens	4', 6' & 8'					Solid Cube			
		6 Direct-Indirect			B 6000lm/4ft C 4400lm/4ft E 3900lm/4ft	L Flush Silk Lens	Q Symmetric Wide-Throw Lens	4', 6' & 8'						Solid Cube		
		1 Surface	1 Direct			G 2600lm/4ft K 1300lm/4ft	L Flush Silk Lens	N None	4', 6' & 8'					Solid Cube		

*Battery packs in 120-277v only, 347v not available. Battery packs are not available in MicroSquare.

Note: QuickShip not available for "Hold for Release" or "Do Not Ship Before" orders.

MAXIMUM 500' PER QUICKSHIP ORDER.

Questions? CS.ledalite@philips.com



Order guide

linear suspended/surface LED continued



SERIES		VERSION		LIGHT SOURCE			OPTICS		BODY	ELECTRICAL			FINISH		MOUNTING	
FAMILY	VERSION	DISTRIBUTION	SOURCE	COLOR TEMP	LUMENS	LOWER OPTICS	UPPER OPTICS	MODULE LENGTH	WIRING TYPE	VOLTAGE	DRIVER	FINISH	ENDS	CEILING KIT	DROP LENGTH	
74 Sync	0 Standard	6 Direct-Indirect	L LED	A 4000k B 3500k C 3000k	A 6500lm/4ft	Q Symmetric MesoOptics	N Lightguide	4' & 8'	7 1 cct w/dimming M 1 cct w/dimming & emergency N 1 cct w/dimming & battery pack*	1 120v 2 277v 3 347v*	E Philips Advance 0-10v (1% dim)	W Standard White T Titanium Silver B Black	Flat	A1	2' 24"	
					C 4600lm/4ft	D 55% Down Kit	A2							adjustable		
					E 3400lm/4ft	G 80% Down Kit	A3							4' 48"		
						J 100% Down Kit	A5							adjustable		
							A6-1							8' 96"		
							A6-2							adjustable		
							A6-3							12' 144"		
							Surface (where available)									
29 TruGroove	0 Standard	1 Direct			E 3200lm/4ft	Q Symmetric MesoOptics	N None	4', 6' & 8'					Sculpted	A6-2		
					G 2300lm/4ft	W Asymmetric MesoOptics										
					K 1500lm/4ft											
76 Verge	0 Standard	6 Direct-Indirect			A 6500lm/4ft	Q MesoOptics Lens	N Lightguide	4' & 8'					Sculpted			
					C 4600lm/4ft		D 55% Down Kit									
					E 3400lm/4ft		G 80% Down Kit									
							J 100% Down Kit									
77 Sona	0 1 Light Chamber - Upper	3 Indirect			C 4900lm/4ft	N Solid (100% up)	A Acrylic Diffuser	4' & 8'					Sculpted			
					E 3400lm/4ft											
77 Sona	1 1 Light Chamber - Lower	1 Direct			B 6100lm/4ft	A Curved Acrylic Diffuser	A Acrylic Diffuser (75% up)	4' & 8'					Sculpted			
					C 4500lm/4ft	V White Louver	D Acrylic Diffuser w/50% Down Kit									
					E 3100lm/4ft											

*Battery packs in 120-277v only, 347v not available. Battery packs are not available in MicroSquare.

Note: QuickShip not available for "Hold for Release" or "Do Not Ship Before" orders.

MAXIMUM 500' PER QUICKSHIP ORDER.

Questions? CS.ledalite@philips.com

